



Transfer Conveyor

Standard Features:

- ***Welded, Structural Steel Frame Construction***
- ***Drives Sized to Match Loads by Factory***
- ***230-460/3/60 Electrical Connection***
- ***High Side, Low Side and Underslung Drive Mounting***
- ***30, 45 and 60 FPM Fixed Conveyor Speed***
- ***Continuously Welded Sprockets***
- ***Rollers Set High on Non-driven Side***
- ***Scalloped Type Roller Chain Guard and #16 Ga. Drive Chain Guard***
- ***Heavy Duty Channel Supports +/- 3/4" Adjustment***
- ***RC-60 or RC-80 Single Rivet Transfer Chains***
- ***Positive Lift by Pneumatic Cylinder***
- ***Double Acting Solenoid Valve Plumbed and Mounted***
- ***Chain Elevation 3/4" Above Rollers***
- ***Painted Alba Blue with Safety Yellow Guards***
- ***Units Typically Shipped Fully Assembled to Minimize Installation Time.***



Optional Items:

- ***Urethane Roller Sleeves***
- ***Zinc Plated, Zinc Flo Coated and Galvanized Rollers***
- ***Blade Stops/Pin Stops***
- ***Photo Eyes***
- ***Wired Devices***
- ***Back Stops/Conveyor Guides***
- ***Fork Truck Barriers***
- ***Transition Rollers***
- ***VFD Rated Drives***
- ***Hot Dipped Galvanized Frames***
- ***Color Match Paint to Specifications***



Transfer Conveyor

Roller Size	Chain	Roller Centers	Transfer Strands		Load	Effective Widths	Lengths	
90° In Frame Style Chain Transfer								
2-1/2" dia. x 11 Ga	RC-40 Chain	3.25"	2	3	2,500 lbs.	4,000 lbs.	44", 48", 52", 54" or 60"	5'-1"
		3.25"						5'-7-1/2"
		3.75"						4'-11-1/4"
		4"						5'-2"
		6"						5'-0"
	RC-60 Chain	3.75"	2	3				5'-0"
		4.5"						4'-10-1/2"
		4.5"						5'-7-1/2"
		6"						5'-0"
								90° Thru Frame Style Chain Transfer
2-1/2" dia. x 11 Ga	RC-40 Chain		3.25"	2	3	2,500 lbs.	4,000 lbs.	44", 48", 52", 54" or 60"
		3.25"	5'-7-1/2"					
		3.75"	4'-11-1/4"					
		4"	5'-2"					
		6"	5'-0"					
	RC-60 Chain	3.75"	2	3	5'-0"			
		4.5"			4'-10-1/2"			
		4.5"			5'-7-1/2"			
		6"			5'-0"			
					90° Frame To Frame Style Chain Transfer			
2-1/2" dia. x 11 Ga	RC-40 Chain		3.25"	2	3	2,500 lbs.	4,000 lbs.	44", 48", 52", 54" or 60"
		3.25"	5'-7-1/2"					
		3.75"	4'-11-1/4"					
		4"	5'-2"					
		6"	5'-0"					
	RC-60 Chain	3.75"	2	3	5'-0"			
		4.5"			4'-10-1/2"			
		4.5"			5'-7-1/2"			
		6"			5'-0"			



Alba Manufacturing, Inc.

8950 Seward Road

Fairfield, Ohio 45011

Phone: (866) 252-2634

Fax: (513) 874-9476

Web: WWW.ALBAMFG.COM