

ALBA ZERO PRESSURE ACCUMULATION CONVEYOR

Standard Chain Driven Live Roller Conveyor Models:

- MZPA251140-3.25
- MZPA251140-4.00
- MZPA251140-6.00

Zero Pressure Accumulation with Individual Motor Driven Zones
Pre-mounted and wired Plug and Play controls. Includes all controls and devices required for basic zero pressure zone accumulation of product.

STANDARD EQUIPMENT SPECIFICATIONS

LENGTH:	5'-0" Nominal zones	ROLLER CAPACITY:	Bed Rollers - 850 Lbs. Each Drive Rollers - 2,100 Lbs. Each	PAINT:	ALBA Standard Blue, with Safety Yellow Chain Guards
WIDTH:	12" - 60" Effective Width	SETTING:	Rollers are set low on driven side and high on other side	ELEVATION:	As low as 6" top of roller when supplied with high side Mounted drives.
ROLLERS:	2-½ diameter x 11 Gauge Wall, 11/16" Hex Axles, Spring Retained, Grease Packed Ball Bearings	DRIVE:	Standard C-Frame Motor and Gear Reducer 230/460/3/60,	SPEED:	30 F.P.M., Fixed
FRAME:	Welded Structural Steel Construction	ROLLER CENTERS:	3-1/4", 4" & 6"		

- OPTIONS:**
- Roller sizes 1.9" , 2-9/16" & 3-1/2" diameter rollers
 - Roller centers
 - Speeds
 - Zero Pressure Zoned Accumulation Controls can be supplied with other types of conveyors such as: Belt Conveyors and Drag Chain Conveyors.

