

ALBA'S VALUE CONVEYOR PROGRAM

Giving you Quality **PRE-ENGINEERED** CDLR Conveyor
More **AFFORDABLE** and **FASTER** Delivery!

Value CDLR Standard Features:

- Welded, structural steel frame construction
- Conveyors for handling up to 4,000 lb
- 230-460/3/60 Electrical connection
- Under slung drive mounting for 18" top of roller
- 5' & 10' sections nominal
- 2 heavy duty SSP3 channel supports +/- 1-3/4" adjustment provided per conveyor at 18" TOR
- 30, 45 or 60 FPM fixed conveyor speed
- Continuously welded sprockets
- Rollers set high on non-driven side
- 10 ga. Scalloped type roller chain guard and 16 ga. drive chain guard
- Painted Alba blue with safety yellow guards
- Conveyors shipped fully assembled to minimize installation time
- Conveyors fully tested prior to shipment
- Conveyors are backed by Alba's standard 2-year warranty

Program Guidelines:

- Contact your National Account Manager for more information on this program.
- No approval drawings are provided. Drawings of pre-engineered equipment can be found on the website and catalog.
- No special widths, lengths or heights can be ordered under this program.
- No options are available under this program.
- No special colors.
- One week ship on most orders (subject to quantity).



Order Number Example:

VC-2511XX-X-X-XX-X - Nominal 5' or 10'

- Speed 30, 45, & 60 FPM
- Effective Width 44" or 52"
- Roller Centers
 - RC-40: 3.25", 3.75", 4", 6"
 - RC-60: 3.75", 4.5", 6"
- Sprocket & Roller Chain Size 40 or 60

Value Conveyor CDLR (Chain Driven Live Roller Conveyor)

PRODUCT SPECIFICATIONS

Alba Model 251140 CDLR Conveyor (850 lb bed roller & 2,100 lb drive roller)			
Order Number	Effective Width	Nominal Length	Conveyor available with 3.25", 3.75", 4" or 6" roller centers
Model 251140	44"	5'	<p>CALL 866.252.2634 FOR CURRENT PRICING AND LEAD TIME</p>
Roller Centers 3.25", 3.75", 4" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
Model 251140	52"	5'	
Roller Centers 3.25", 3.75", 4" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
<p>Order Number Example (251140-3.25-44-30-5) 2,500 lb max load 2 1/2" dia. x 11 ga. rollers, 11/16" hex axles spring retained rollers, 1/2 hp Baldor motor with Dodge Tigear-2 reducer, 230-460/3/60, Rollers are set high on non-driven side, two (2) supports, 18" top of roller, Alba blue with safety yellow guards.</p>			
Alba Model 251160 CDLR Conveyor (850 lb bed roller & 2,100 lb drive roller)			
Order Number	Effective Width	Nominal Length	Conveyor available with 3.75", 4.5" or 6" roller centers
Model 251160	44"	5'	<p>CALL 866.252.2634 FOR CURRENT PRICING AND LEAD TIME</p>
Roller Centers 3.75", 4.5" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
Model 251160	52"	5'	
Roller Centers 3.75", 4.5" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
<p>Order Number Example (251160-3.75-44-30-5) 4,000 lb max load 2 1/2" dia. x 11 ga. rollers, 11/16" hex axles spring retained rollers, 3/4 hp Baldor motor with Dodge Tigear-2 reducer, 230-460/3/60, Rollers are set high on non-driven side, two (2) supports, 18" top of roller, Alba blue with safety yellow guards.</p>			

*Alba reserves the right to make changes to the program at any time. Copyright ©2026 by Alba Manufacturing



Alba Manufacturing, Inc.
8950 Seward Road, Fairfield, Ohio 45011

866.252.2634
rocksolidconveyor@albamfg.com
www.albamfg.com