

ALBA's VALUE CONVEYOR PROGRAM

Giving you Quality **PRE-ENGINEERED** CDLR Conveyor
More **AFFORDABLE** and **FASTER** Delivery!

Value CDLR Standard Features:

- Welded, structural steel frame construction.
- Conveyors for handling up to 4,000 lbs.
- 230-460/3/60 Electrical connection.
- Under slung drive mounting for 18" top of roller.
- 5' & 10' sections nominal.
- 2 heavy duty SSP3 channel supports +/- 1-3/4" adjustment provided per conveyor @ 18" TOR.
- 30, 45 or 60 FPM fixed conveyor speed
- Continuously welded sprockets.
- Rollers set high on non-driven side.
- #10 ga. Scalloped type roller chain guard and #16 ga. drive chain guard.
- Painted Alba blue with safety yellow guards.
- Conveyors shipped fully assembled to minimize installation time.
- Conveyors fully tested prior to shipment.
- Conveyors are backed by Alba's standard 2-year warranty.

Program Guidelines:

- Contact your National Account Manager for more information on this program.
- No approval drawings are provided. Drawings of pre-engineered equipment can be found on the website and catalog.
- No special widths, lengths or heights can be ordered under this program.
- No options are available under this program.
- No special colors.
- One week ship on most orders (subject to quantity).



Order Number Example:

VC-2511XX-X-X-XX-X - Nominal 5' or 10'

└─ Speed 30, 45, & 60 FPM

└─ Effective Width 44" or 52"

└─ Roller Centers ┌─ RC-40
 3.25", 3.75", 4", 6"

 └─ RC-60
 3.75", 4.5", 6"

└─ Sprocket & Roller Chain Size 40 or 60



866.252.2634
www.albamfg.com
rocksolidconveyor@albamfg.com



Value Conveyor CDLR (Chain Driven Live Roller Conveyor)

PRODUCT SPECIFICATIONS

Alba Model 251140 CDLR Conveyor (850 lb bed roller & 2,100 lb drive roller)			
Order Number	Effective Width	Nominal Length	Conveyor available with 3.25", 3.75", 4" or 6" roller centers
Model 251140	44"	5'	CALL 866.252.2634 FOR CURRENT PRICING AND LEAD TIME
Roller Centers 3.25", 3.75", 4" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
Model 251140	52"	5'	
Roller Centers 3.25", 3.75", 4" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
Order Number Example (251140-3.25-44-30-5) 2,500 lb max load 2 1/2" dia. x 11 ga. rollers, 11/16" hex axles spring retained rollers, 1/2 hp Baldor motor with Dodge Tigear-2 reducer, 230-460/3/60, Rollers are set high on non-driven side, two (2) supports, 18" top of roller, Alba blue with safety yellow guards.			
Alba Model 251160 CDLR Conveyor (850 lb bed roller & 2,100 lb drive roller)			
Order Number	Effective Width	Nominal Length	Conveyor available with 3.75", 4.5" or 6" roller centers
Model 251160	44"	5'	CALL 866.252.2634 FOR CURRENT PRICING AND LEAD TIME
Roller Centers 3.75", 4.5" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
Model 251160	52"	5'	
Roller Centers 3.75", 4.5" & 6"		10'	
Speed 30, 45 or 60 FPM			
Length 5'-0" or 10'-0" long			
Order Number Example (251160-3.75-44-30-5) 4,000 lb max load 2 1/2" dia. x 11 ga. rollers, 11/16" hex axles spring retained rollers, 3/4 hp Baldor motor with Dodge Tigear-2 reducer, 230-460/3/60, Rollers are set high on non-driven side, two (2) supports, 18" top of roller, Alba blue with safety yellow guards.			

*Alba reserves the right to make changes to the program at any time. Copyright ©2022 by Alba Manufacturing



Alba Manufacturing, Inc.
8950 Seward Road, Fairfield, Ohio 45011

866.252.2634
rocksolidconveyor@albamfg.com
www.albamfg.com
VC-CDLR06082022